

MAINTENANCE AND PROTECTION OF ASTONLOUIS LAMINAT PARQUETS

Never apply in damp or wet environments. Since the closed surface of Astonlouis laminate flooring generally prevents dirt from penetrating deep into the flooring. Cleaning AstonLouis parquet with water can cause undesirable swelling of parquets. When -you are choosing your cleaning products be sure they are not contains oil and wax. Unlike solid parquets, oil and wax penetrate the surface of the laminate flooring and remain a thin layer on the Parquet. This film may cause unwanted fine cracks on the surface and may show footprints

For regular maintenance of AstonLouis laminate flooring, it is necessary to periodically vacuum your laminate and wipe it with a dry cloth. If necessary, you can wipe the floor every two weeks with a damp cloth. Use laminate flooring cleaning material, then rinse the cloth thoroughly, and then wipe the floor with a dry cloth. When using a solvent or condensed cleaning solution, read the safety recommendations first! (Never use bleach)

Below you will find recommendations for removing stains on Astonlouis Laminate flooring.

Gum and wax stains can be removed using a plastic scraper (not sharp). After the stain hardens from Laminat flooring.

Removal of stains from fruit, milk, alcohol, rubber, plastic, heel and foodstuff from laminate; Remove the stain using a dry absorbent cloth. If the stain is dried, clean it with the appropriate cleaning solution, and then wipe it dry with a dry cloth.

Use felt bolts and rubber chair rollers for furniture legs to preserve the value of your laminate floor. Suitable for castor chairs with DIN 68131 Type 'w'.

Room temperature should be 18-22 C, air humidity 50-60%.